



# TAILS

## ULTRASPRING POLYESTER

Long life cycle jacketed mooring tail or towing stretcher.

### FEATURES

- **Material:** Polyester
- **Construction:** One load-bearing core with a protective cover of composite yarn
- **Treatment:** On request
- **Color of Rope:** White
- **Approx. Spec. Density:** 1,38 non-floating
- **Melting Point:** 260° C
- **Abrasion Resistance:** Excellent
- **U.V. resistance:** Excellent, due to jacket
- **Temperature resistance:** 80°C max continuous
- **Chemical resistance:** Good, bases and solvents may have a mild effect
- **Dry & wet conditions:** Wet strength equals dry strength

ULTRASPRING POLYESTER					
Dia	Circ.	Dia	Min. Break Load		Weight
mm	“	“	tf	kN	kg/100m
32	4	1 <sup>5</sup> / <sub>16</sub>	27.5	270	70.8
36	4 1/2	1 1/2	34.4	337	86.2
40	5	1 <sup>5</sup> / <sub>8</sub>			
44	5 1/2	1 <sup>3</sup> / <sub>4</sub>	48.1	472	124
48	6	2	53.7	527	137
52	6 1/2	2 <sup>1</sup> / <sub>8</sub>	67.2	659	166
56	7	2 <sup>1</sup> / <sub>4</sub>	80.6	791	194
60	7 1/2	2 <sup>1</sup> / <sub>2</sub>	94.0	922	222
68	8 1/2	2 <sup>3</sup> / <sub>4</sub>	107	1054	264
72	9	3	134	1318	317
76	9 1/2	3 <sup>1</sup> / <sub>8</sub>			
80	10	3 <sup>1</sup> / <sub>4</sub>	161	1581	390
88	11	3 <sup>5</sup> / <sub>8</sub>	188	1845	449
96	12	4	215	2108	534
104	13	4 <sup>1</sup> / <sub>4</sub>	269	2635	645





## CONTACT



BEXCO NV  
Industriepark Zwaarveld 25  
9220 Hamme  
Belgium  
Tel: + 32 52 499 370  
E-mail: [sales@bexco.be](mailto:sales@bexco.be)  
For more information on our products:  
[www.bexco.be](http://www.bexco.be)

**BEXCO**  
OUR ROPE, YOUR SOLUTION