



TAILS

ULTRASPRING POLYESTER

Long life cycle jacketed mooring tail or towing stretcher.

FEATURES

- **Material:** Polyester
- **Construction:** One load-bearing core with a protective cover of composite yarn
- **Treatment:** On request
- **Color of Rope:** White
- **Approx. Spec. Density:** 1,38 non- coating
- **Melting Point:** 260° C
- **Abrasion Resistance:** Excellent
- **U.V. resistance:** Excellent, due to jacket
- **Temperature resistance:** 80°C max continuous
- **Chemical resistance:** Good, bases and solvents may have a mild effect
- **Dry & wet conditions:** Wet strength equals dry strength

ULTRASPRING POLYESTER					
Dia	Circ.	Dia	Min. Break Load		Weight
mm	“	“	tf	kN	kg/100m
32	4	1 5/16	27.5	270	70.8
36	4 1/2	1 1/2	34.4	337	86.2
40	5	1 5/8			
44	5 1/2	1 3/4	48.1	472	124
48	6	2	53.7	527	137
52	6 1/2	2 1/8	67.2	659	166
56	7	2 1/4	80.6	791	194
60	7 1/2	2 1/2	94.0	922	222
68	8 1/2	2 3/4	107	1054	264
72	9	3	134	1318	317
76	9 1/2	3 1/8			
80	10	3 1/4	161	1581	390
88	11	3 5/8	188	1845	449
96	12	4	215	2108	534
104	13	4 1/4	269	2635	645



