



TAILS

ULTRASPRING POLYAMIDE

High quality jacketed mooring tail.

FEATURES

- **Material:** Polyamide (nylon)
- **Construction:** One load-bearing core with a protective cover of composite yarn
- **Treatment:** On request
- **Color of Rope:** White
- **Approx. Spec. Density:** 1,14 non-floating
- **Melting Point:** 215° C
- **Abrasion Resistance:** Excellent
- **U.V. resistance:** Excellent, due to jacket
- **Temperature resistance:** 80°C max continuous
- **Chemical resistance:** Reasonable; acids, oxidizers and solvents will affect the material
- **Dry & wet conditions:** Wet strength about 5% lower than dry strength

ULTRASPRING POLYAMIDE					
Dia	Circ.	Dia	Min. Break Load		Weight
mm	"	"	tf	kN	kg/100m
32	4	1 ⁵ / ₁₆	23.2	228	62.3
36	4 1/2	1 1/2	29.0	285	75.6
40	5	1 ⁵ / ₈	33.8	332	92.9
44	5 1/2	1 ³ / ₄	40.6	398	109
48	6	2	45.1	443	120
52	6 1/2	2 ¹ / ₈	56.4	553	144
56	7	2 ¹ / ₄	67.7	664	168
60	7 1/2	2 1/2	79.0	775	193
68	8 1/2	2 ³ / ₄	90.3	885	230
72	9	3	113	1107	275
80	10	3 ¹ / ₄	135	1328	339
88	11	3 ⁵ / ₈	158	1549	390
96	12	4	181	1771	465
104	13	4 ¹ / ₄	226	2213	560



CONTACT



BEXCO NV
Industriepark Zwaarveld 25
9220 Hamme
Belgium
Tel: + 32 52 499 370
E-mail: sales@bexco.be
For more information on our products:
www.bexco.be

B E X C O

OUR ROPE, YOUR SOLUTION